

# Alliance

# Endurance

## Long Lasting Floor Finish



18% Solids Floor Finish

A styrene free, extremely durable sealer/finish designed for stone floors, terrazzo, quarry tile, brick, slate, stone, Mexican tile, VCT and other types of flooring. Leaves these surfaces with a durable, high quality, long lasting, protective coating. The styrene free formula allows the finish to dry clear, seals, and protects the beauty of the floor.

### DIRECTIONS

**PREPARATION:** If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely.  
If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

**FINISHING:** Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Five coats is ideal initially, depending on the condition of the floor and desired gloss.

**MAINTENANCE:** The floor may be maintained using a quality floor cleaner and damp mopping/auto-scrubbing regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.  
This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations.

### PRODUCT SPECIFICATIONS

|                             |                                    |                               |                           |
|-----------------------------|------------------------------------|-------------------------------|---------------------------|
| <b>Color:</b>               | White                              | <b>Maintenance Schedule:</b>  | Daily cleaning            |
| <b>Odor:</b>                | Fragrance free                     | <b>Slip Resistance:</b>       | 0.5 min. by<br>ASTM-D2047 |
| <b>pH:</b>                  | 8.0 – 9.0                          | <b>Storage/Stability:</b>     | 1 year                    |
| <b>Non-Volatile Solids:</b> | 18%                                | <b>Weight Per Gallon:</b>     | 8.59 lbs./gal.            |
| <b>Coverage:</b>            | 1800 – 2200 ft <sup>2</sup> / gal. | <b>Freeze/Thaw Stability:</b> | 3 cycles                  |
| <b>Recommended Coats:</b>   | 2 - 5                              |                               |                           |
| <b>Dry/Recoat Time:</b>     | 30 minutes min.                    |                               |                           |



Sold by: 4-State Maintenance Supply, Inc.  
503 N. Cline Rd.  
Coffeyville, KS 67337  
Phone: 1-800-497-5707 or 620-251-7033  
Fax: 620-251-0391  
Email: support@4statemaintenance.com