

# Alliance

## Hi-Shine

### High Solids Ultra-Compatible Floor Finish



25% Solids Floor Finish

A new generation floor finish formulated with a patented polymer technology that is designed to work with many maintenance programs and equipment on all types of floors due to its ultra-compatibility and flexibility. This high-solids finish requires fewer coats and provides superior gloss, excellent durability and superior leveling. New chemistry allows the finish to form good film even in poor drying conditions. Excellent response with any type of UHS equipment - propane, battery, or cord electric. Easy to apply and ideal for routine burnishing.

#### DIRECTIONS

**PREPARATION:** If stripping is necessary, use a high quality stripper and follow the directions accordingly. Follow with a thorough rinsing and allow floor to dry completely. If stripping is not necessary; sweep up loose dirt and dust. Clean with a quality cleaner to remove dirt and oils. Follow with a thorough rinsing and allow floor to dry completely.

**FINISHING:** Spread a liberal coat of finish evenly across the floor with a clean mop or applicator. Allow each coat to dry at least 30 minutes before applying the next coat. Four coats are ideal initially, depending on the condition of the floor and desired gloss.

**MAINTENANCE:** The floor may be maintained using a quality floor cleaner and damp mopping/auto-scrubbing regularly. Spray buffing or mop-on restoring may also be done after sweeping up loose dirt and dust. Follow directions for each product accordingly.

This product meets the maximum content requirements for Volatile Organic Compounds (VOCs) as established by state and Federal regulations

#### PRODUCT SPECIFICATIONS

<b>Non-volatile Solids:</b>	25.0 ± 0.5%	<b>Coverage:</b>	Up to 2000-2500 sq. ft. per gal.
<b>Color:</b>	Milky emulsion	<b>Removability:</b>	With instant type strippers
<b>Odor:</b>	Mild	<b>Detergent Resistance:</b>	Excellent
<b>pH:</b>	8.0 – 9.0	<b>Heel Mark Resistance:</b>	Excellent
<b>Dry/Recoat Time:</b>	30 minutes	<b>VOC Content:</b>	0.48 lbs./gal.
<b>Slip Resistance:</b>	0.5 min. by ASTM-D2047	<b>Storage/Stability:</b>	1 years
<b>Leveling:</b>	Excellent	<b>Weight Per Gallon:</b>	8.66 lbs./gal.
<b>Buffability:</b>	Dry Burnish/ Spray Buff	<b>Freeze/Thaw Stability:</b>	Keep from freezing



Sold by: 4-State Maintenance Supply, Inc.  
503 N. Cline Rd.  
Coffeyville, KS 67337  
Phone: 1-800-497-5707 or 620-251-7033  
Fax: 620-251-0391  
Email: support@4statemaintenance.com